

GEAR UNIT CABINET

Lighting gear unit cabinet suitable for outdoor and indoor installation. Each gear unit cabinet can have the gear units of nine light engines.

Several gear unit mounting options. Power supply can be concatenated, standard 2xAl/Cu 1.5...50mm² coupling. Cabling from below. The gear unit's heating and air circulation equalizes temperatures and prevents condensation inside the gear unit. The unit can be fitted with several lighting control systems. The unit socket outlet has a protection device for fault currents.

Gear unit cabinet dimensions

Width	Height	Depth
360mm	1500mm	320mm

TECHNICAL SPECIFICATIONS

Weight	Approx. 58kg
Width	360mm
Height	1500mm
Depth	320mm
Operating temperature	-40...+35°C
Protection class	IP66
Installation method	Wall mounting / Pole mounting / Plinth mounting
Cabinet material	Steel coated with polyester paint / Stainless steel
Cabinet locking	Bolt / Several lock options

ELECTRICAL SPECIFICATIONS

Nominal voltage	$U_N=400V$
Frequency	$f=50Hz$
Nominal current	$I_{NA}=40A$
Short circuit protection	$I_{CW}<6kA$
Contact control voltage	230V
Heating and air circulation	Standard
Connectors and wires	L1,L2,L3,N,PE/PEN
Lighting control	Several options
Cabling	Can be concatenated / With a cable entry from below
Cable output	With a cable entry from below



Easy LED Oy

Meriniitynkatu 11

FI-24100 Salo, FINLAND

tel. +358 2 737 44 20

easyled.fi

