BASE BUBO

EASY LED



BUBO BASE TWIN -GEAR UNIT CABINET 7–15

A gear unit cabinet suitable for both outdoor and indoor installations. With the double cabinet, the number of gear units can be increased to fifteen. The control of the gear units can be implemented according to DALI-2 and D4i standards. The drivers are Zhaga compatible. Separate Zhaga connectors for mast installations, available on request.

Several gear units mounting options. Power supply can be concatenated, standard 2xAl/Cu 1,5...50mm^2 or 2xAl/Cu 25...150mm^2 coupling. Cabling from below. The gear unit's heating and air circulation equalizes temperature and prevents condensation inside the gear unit. Option to equip with a RCD (residual current device) protected sockets and a separate heater.

TECHNICAL SPECIFICATIONS

Weight	145 kg
Width	821 mm
Height	1500 mm
Depth	210 mm
Operating temperature	-40...+35˚C
Protection class	IP66/IP65
Impact resistance	IK 09
Installation method	Wall mounting / Pole mounting / Plinth mounting
Cabinet material	Steel coated with polyester paint / AISI304 / AISI316
Cabinet locking	Bolt / Several lock options

ELECTRICAL SPECIFICATIONS

Nominal voltage	U_N=400V
Frequency	f=50Hz
Nominal current	I_{NA}=63A
Short circuit protection	I_{CW}<10kA
Contactor control voltage	230 V
Air circulation	Standard
Heating	Optional
Connectors and wires	L1,L2,L3,N,PE
Lighting control	Several options
Cabling	Can be concatenated / With a cable entry from below
Cable output	With a cable entry from below
RCD-protected sockets	Optional

Easy LED Oy
Meriniitynkatu 11
FI-24100 Salo, FINLAND
tel. +358 2 737 44 20
easyled.fi

We reserve the right for changes © Easy LED Oy 2025